

SECURITY FIXTURES

LAVATORY FIXTURE - 5113

ltem:	 ٤
	O



☐ 5113 Rear-Mounted Security Lavatory

STANDARD FEATURES

- Chase mounted fixture, wall outlet waste.
- Lavatory basin-
 - · Rectangular lavatory basin
 - · Multi-hole integral drain.
 - Stainless steel elbow waste with 11/4" (32mm) OD plain end extended 4" (102mm) past back of fixture.
- 4" (102mm) high back splash.
- Integrally welded bottom enclosure.
- Penal bubbler.
- Drip dimple.
- Hardware-
 - Plated steel concealed anchor rods and fasteners.

Unit may be pictured with some optional features.



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

▶ DESCRIPTION

This lavatory fixture is designed for areas with an accessible pipe chase. The fixture is fabricated using 14 gauge type 304 stainless steel, welded to form a vandal resistant unit. Internal piping is stainless steel. Lavatory is designed with a 4" (102mm) high backsplash. Exposed surfaces are polished to a satin finish. Valves and valve outlets must be specified separately.

▶ PERFORMANCE STANDARDS

This fixture meets or exceeds ASME A112.19.3 / CSA B45.4 standards for "Stainless Steel Plumbing Fixtures".

► INSTALLATION

An accessible pipe chase is required. Four anchor rods are screwed into sockets on back of the fixture. Anchor rods pass through the wall and are secured from the pipe chase using washers and hex nuts provided. The installer must provide wall openings for anchor rods, piping and valve operators per rough-in drawings provided by Metcraft. Valves should be installed in the pipe chase. Fixture is handicap compliant when installed per quidelines for accessibility.

NOTE: A security frame (wall sleeve) is recommended when installed on a new block (CMU) or poured concrete wall. A security frame is not appropriate for hollow wall construction.

Listed by



SECURITY FIXTURES

WALL THICKNESS AND TYPE (Must Specify)				
Thick	ness:	Type: Concrete Block Steel		
SP0	UTS			
╚	B1	Penal filler/bubbler.		
	B1H	Suicide Resistant filler/bubbler.		
	B2	Filler/bubbler with mouthguard.		
	ВЗН	Suicide Resistant filler.		
HAN	ID BASINS			
	ОВ	Oval Basin		
	RB	Rectangular Basin (Standard)		
LAV	ATORY WAS	ГЕ		
	EPE	Elbow Waste Plain End. (Standard)		
	EPL	Elbow Waste Plain End through the wall.		
	ET2	Elbow Waste.		
	PPE	P-Trap Plain End.		
	PPL	P-Trap Plain End through the walls.		
	PT2	P-Trap.		
LAV	ATODV 14/A C	TE EVTENCIONIC		
LAV	LAVATORY WASTE EXTENSIONS			
J	A235	Trap Assembly.		

Waste Extension 1-1/2"

A240

	A120	Security Frame (Wall Sleeve/Can).		
	A168	Metal Template for Wall Openings.		
	HT	Towel Hook.		
	ТВ	Toothbrush Holder.		
	0F	Overflow Vent.		
	PCC	Powder Coat - Anti-microbial White.		
LAV	ATORY WAS	TE ADAPTER COUPLINGS		
Ц	A205-1	Lavatory waste coupling 1-1/4" (32mm) s/s to 1-1/2" (38mm) COPPER		
	A205-2	Lavatory waste coupling 1-1/4" (32mm) s/s to 1-1/2" (38mm) PL/STL		
	A205-3	Lavatory waste coupling 1-1/4" (32mm) s/s to 2" (51mm) CI		

PNEUMATIC VALVE ASSEMBLIES (0.5 GPM Flow Valves)

A311 Single Temperature, Single Fixture Valve.

A312 Dual Temperature, Single Fixture Valve.


A313 Single Temperature, Manifold Fixture Valve.

Dual Temperature, Manifold Fixture Valve.


OPTIONAL ACCESSORIES

Note: To mount lavatory in accordance with "Handicap" requirements the rim height must be mounted at 34" (864mm) above finished floor.

LAVATORY FIXTURE - 5113



Due to continuous product improvement Metcraft reserves the right to make changes in design and specifications without prior notice. All dimensions should be verified with the factory for current information.



APPROVED FOR	Company:_	Name:
MANUFACTURING	Signature:	Date: